



NCV 10-22 CORDLESS INTERNAL CONCRETE VIBRATOR WHIP PORTFOLIO OVERVIEW

Basic information				Key applications						Item information		
Head diameter	Whip length	Weight		Deck and flatwork	Shallow footings	Deep footings	Curbs	Walls and columns	Concrete yards - small elements	Concrete yards - large elements	Item name	EU/ROW Item no.
IP 67 classification – Protection against short periods of immersion while under pressure												
Motor in head/high frequency concrete vibrating whips for NCV 10-22	1 1/2" / 38 mm	5 ft. / 1.5 m	9.5 lb / 4.3 kg								NCV 38 × 1500-1.5 × 5	2404614
	1 1/2" / 38 mm	10 ft. / 3 m	11.7 lb / 5.3 kg								NCV 38 × 3000-1.5 × 10	2404615
	1 1/2" / 38 mm	16 ft. / 5 m	14.8 lb / 6.7 kg								NCV 38 × 5000-1.5 × 16	2404616
	1 3/4" / 45 mm	5 ft. / 1.5 m	12.1 lb / 5.5 kg								NCV 45 × 1500-1.75 × 5	2404617
	1 3/4" / 45 mm	10 ft. / 3 m	14.3 lb / 6.5 kg								NCV 45 × 3000-1.75 × 10	2404618
	1 3/4" / 45 mm	16 ft. / 5 m	17.4 lb / 7.9 kg								NCV 45 × 5000-1.75 × 16	2404619
	2 1/4" / 58 mm	5 ft. / 1.5 m	17.9 lb / 8.1 kg								NCV 58 × 1500-2.25 × 5	2404611
	2 1/4" / 58 mm	10 ft. / 3 m	21.4 lb / 9.7 kg								NCV 58 × 3000-2.25 × 10	2404612
	2 1/4" / 58 mm	16 ft. / 5 m	26.2 lb / 11.9 kg								NCV 58 × 5000-2.25 × 16	2404613

■ recommended
 ■ use possible
 ■ not recommended

